

## Topla Top

### ORDER INFORMATION

|                             |            |
|-----------------------------|------------|
| Short code                  | TT55H      |
| TAB ID                      | 118655     |
| DIN marking                 | 55510 SMF  |
| Quantity per EUR/CNT pallet | 60/100 Pcs |

### TECHNICAL INFORMATION

|              |       |
|--------------|-------|
| Voltage      | 12 V  |
| Capacity C20 | 55 Ah |
| CCA -18°C EN | 550 A |

### DIMENSION AND WEIGHTS




|                     |                |
|---------------------|----------------|
| Length/Width/Height | 207x175x190 mm |
| Total weight        | 13.2 kg        |

### TECHNOLOGY


|             |                        |
|-------------|------------------------|
| Type        | Flooded                |
| Grid type   | Expanded               |
| Grid alloy  | Ca/Ca                  |
| Separator   | PE                     |
| Electrolyte | 1.28 g/cm <sup>3</sup> |

### BOX DESIGNS

|                |       |
|----------------|-------|
| Container type | L1    |
| Colour         | Black |
| Polarity       | 0     |
| Base hold down | B13   |
| Cover type     | SMF   |
| Layout         | 0     |
| Terminal       | 1     |



#### Base hold down



#### Layout

